

Revision date: 2007/07/31 Page: 1/6
Version: 1.0 (30322607/MDS\_GEN\_US/EN)

# 1. Substance/preparation and company identification

Company
BASF CORPORATION
100 Campus Drive
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP

# 2. Composition/information on ingredients

CAS Number	Content (W/W)	Chemical name
12001-26-2	38.0 - 65.0 %	Mica-group minerals
13463-67-7	24.0 - 36.0 %	titanium dioxide
1317-61-9	10.0 - 26.0 %	Iron oxide (Fe3O4)
1309-37-1	1.0 - 10.0 %	Iron oxide

# 3. Hazard identification

### **Emergency overview**

CAUTION: Prolonged or repeated exposure may cause pulmonary problems. Avoid inhalation of dusts.

Ensure adequate ventilation.

#### Potential health effects

### Primary routes of exposure

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

## Irritation:

Inhalation of dust may cause respiratory tract irritation, coughing and breathing difficuties. Contact with the eyes or skin may cause mechanical irritation.

# Potential environmental effects

## Aquatic toxicity:

At the present state of knowledge, no negative ecological effects are expected.

Revision date : 2007/07/31 Page: 2/6 Version: 1.0 (30322607/MDS\_GEN\_US/EN)

# 4. First-aid measures

#### **General advice:**

Remove contaminated clothing.

#### If inhaled:

If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention.

#### If on skin:

Wash thoroughly with soap and water.

#### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

#### If swallowed:

Rinse mouth and then drink plenty of water.

### Note to physician

Treat according to symptoms (decontamination, vital functions), no known

specific antidote.

# 5. Fire-fighting measures

Autoignition: Not applicable

Flammability: does not ignite

#### Suitable extinguishing media:

dry extinguishing media, foam

# Unsuitable extinguishing media for safety reasons:

carbon dioxide

## Hazards during fire-fighting:

No particular hazards known.

# Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

#### **Further information:**

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

If exposed to fire, keep containers cool by spraying with water.

# 6. Accidental release measures

#### Personal precautions:

Avoid dust formation.

Wear appropriate respiratory protection. Use personal protective clothing. Ensure adequate ventilation.

## **Environmental precautions:**

Do not empty into drains.

Revision date : 2007/07/31 Page: 3/6
Version: 1.0 (30322607/MDS\_GEN\_US/EN)

This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund').

#### Cleanup:

For small amounts: Pick up with suitable appliance and dispose of. For large amounts: Pick up with suitable appliance and dispose of.

Spills should be contained and placed in suitable containers for disposal.

# 7. Handling and storage

# **Handling**

#### General advice:

Breathing must be protected when large quantities are decanted without local exhaust ventilation. Avoid contact with the skin, eyes and clothing.

Avoid dust formation. Closed containers should only be opened in well-ventilated areas.

### Protection against fire and explosion:

No special precautions necessary.

See MSDS section 5 - Fire fighting measures. Prevent electrostatic charge accumulation.

#### Storage

Iron oxide

#### General advice:

Keep in a cool place. Keep container dry.

# 8. Exposure controls and personal protection

# Components with workplace control parameters

Mica-group minerals OSHA TWA value 20 millions of particles per cubic foot of air ;

ACGIH TWA value 3 mg/m3 Respirable fraction;

titanium dioxide OSHA PEL 15 mg/m3 Total dust ;

ACGIH TWA value 10 mg/m3;

ACGIH TWA value 5 mg/m3 Respirable fraction;

# Personal protective equipment

## Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

### Hand protection:

Chemical resistant protective gloves

#### Eye protection:

Safety glasses with side-shields.

# General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Due to the colouring properties of the product closed work clothes should be used, to avoid stains during manipulation. Hands and/or face should be washed before breaks and at the end of the shift. Wash soiled clothing immediately.

Revision date : 2007/07/31 Page: 4/6
Version: 1.0 (30322607/MDS\_GEN\_US/EN)

# 9. Physical and chemical properties

Form: powder
Odour: odourless
Colour: yellowish to grey

pH value: 7.0 - 11.0 (4 %(m))

Melting point:

The substance / product decomposes.

Density: 3.3 kg/l
Relative density: 3.3
Bulk density: 218 kg/m3
Particle size: 6 - 90 µm

Solubility in water: insoluble

# 10. Stability and reactivity

#### **Hazardous reactions:**

No hazardous reactions when stored and handled according to instructions.

The product is chemically stable.

Hazardous polymerization will not occur.

## **Decomposition products:**

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

## Thermal decomposition:

No data available.

# 11. Toxicological information

# **Acute toxicity**

Oral:

LD50/rat: > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

....p..........

Skin irritation:

May cause mechanical irritation.

Eye irritation:

May cause mechanical irritation.

# 12. Ecological information

### **Environmental fate and transport**

**Biodegradation:** 

Evaluation: The colourant is insoluble in water and can thus be separated from water

mechanically in suitable effluent treatment plant

### Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

### **Environmental toxicity**

Revision date : 2007/07/31 Page: 5/6 Version: 1.0 (30322607/MDS\_GEN\_US/EN)

#### Other ecotoxicological advice:

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

# 13. Disposal considerations

### Waste disposal of substance:

Must be dumped or incinerated in accordance with local regulations.

Dispose of in a licensed facility.

Do not discharge into drains/surface waters/groundwater.

It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

### Container disposal:

Uncontaminated packaging can be re-used. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

# 14. Transport information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

**IMDG** 

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

# 15. Regulatory information

## **Federal Regulations**

Registration status:

TSCA, US released / listed

SARA hazard categories (EPCRA 311/312): Acute

## State regulations

State RTK

CAS NumberChemical nameState RTK12001-26-2Mica-group mineralsMA, NJ, PA13463-67-7titanium dioxideMA, NJ, PA

Revision date : 2007/07/31 Page: 6/6

 Version: 1.0
 (30322607/MDS\_GEN\_US/EN)

### 16. Other information

**HMIS III rating** 

Health: 1 Flammability: 0 Physical hazard: 0

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

#### Local contact information

Prod\_Reg@basf.com

Mearlin® NU-Antique Gold 9212GB is a registered trademark of BASF Corporation or BASF AG IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

Due to the merger of Engelhard Corp. and BASFGroup all Material Safety Data Sheets have been reassessed on the basis of consolidated information. This may have resulted in changes of the Material Safety Data Sheets. In case you have questions concerning such changes please contact us under the address mentioned in Section I.

**END OF DATA SHEET**